

USE TILT KIT OPTION FOR INSTALLATIONS THAT REQUIRE MODULES TO BE TILTED ABOVE THE EXISTING ROOF SLOPE

MEDIUM TILT SYSTEM SHOWN IS DESIGNED FOR TILT ANGLES FROM 0 TO 20 DEGREES ABOVE ROOF SURFACE

INSTALL ALL L-FEET IN ORIENTATION SHOWN

TORQUE $\frac{5}{16}$ " \varnothing HARDWARE TO THE FOLLOWING MINIMUM VALUES UNLESS OTHERWISE NOTED:
 - SILVER S.S. 16 FT-LBS
 - BLACK S.S. 9 FT-LBS

REFER TO ENGINEERING CHARTS FOR RAIL SPAN BASED ON MODULE TILT ANGLE, WIND SPEED, AND SNOW LOAD

FOR MODULE OVERHANG REQUIREMENTS SEE "S100-D07 TYPICAL LAYOUT"

FOR LEVELING REQUIREMENTS SEE "S100-D08 RAIL LEVELING"

*A SITE-SPECIFIC ANALYSIS IS REQUIRED IF A TALLER STANDOFF IS NECESSARY FOR PROPER INSTALLATION

REVISION:		
A	11/28/2017	NEW ITEM ECF

